ZC10L RFID ENABLED



LARGE FORMAT CARD PRINTER

The Zebra ZC10L industrial card printer is designed to meet the needs of the hospitality industry.

The ZC10L is the only large-format (3.46" x 5.5"), direct-to-card printer that can print edge-to-edge in full color.

The ZC10L is a must-have for any event planner!



-3.46" -

AB&R® ZEBRA ZC10L ENHANCEMENTS







RFID OPTIONS
NOW AVAILABLE

- HF RFID
- UHF RFID
- Ethernet connectivity

APPLICATIONS

- Conferences
- Access Control
- Personnel Tracking
- Sporting Events
- Concerts
- Festivals

On-demand RFID encoding and printing gives you the freedom to customize RFID credentials for each individual attending your event, and with 300 dpi print quality, the ZC10L enables you to produce 5.5" x 3.46" cards with exceptional photo-quality images, rich colors, and crisp text.

DOES THE ZC10L RFID ENABLED PRINTER MAKE SENSE FOR YOUR BUSINESS?

CONTACT AB&R® 800-281-3056



Printer Repair

Specialist

PROVEN SOLUTIONS THAT DRIVE EFFICIENCY AND PRODUCTIVITY IN YOUR SUPPLY CHAIN

www.abr.com



ZC10L RFID ENABLED SPECIFICATIONS



LARGE FORMAT CARD PRINTER

PRINTING		

- Direct to card dye diffusion
- · Full color or monochrome printing
- · Single-sided printing
- Max print speed single-side YMCKO 195 cph*
- Max print speed single-sided K mono 360-410 cph*
- · Photo-quality images
- · Edge-to-edge printing

STANDARD FEATURES

- USB connectivity
- · 200 card (24 mil) capacity feeder
- 70 card capacity output hopper
- · Multi-status LED operator display
- 300 dpi print resolution
- 64 MB memory standard
- 2 year / 20,000 card warranty on printer
- Zebra CardStudio 2.0 card design and issuance software (30 day trial)
- · Microsoft® Windows® drivers
- UHF RFID Encoding
- NFC RFID Encoding

OPTIONS AND ACCESSORIES

Zebra OneCare Service program 10/1000 Ethernet connectivity

SOFTWARE

Windows 7, Windows 8.1 and Windows 10

CardStudio Classic version 1.3 or later card design and issuance software single user license key

API supporting RFID encoding and Ethernet communications		
Driver Features	Auto sensing of ribbon type Remaining card count on ribbon	
SUPPLIES		
Intelligent technology uses RFID tags to authenticate and automate color ribbon and monochrome ribbon.		
Ribbon	YMCO 4-panel: 400 images/roll Monochrome	

CARD SPECIFICATIONS		
Card Thickness	17 mil	
Card Size	5.5" x 3.46" (140 mm x 88 mm)	
Card Material	PVC	
Smart Cards	HF, UHF, Dual HF/UHF	
	-	

COMMUNICATIONS INTERFACES

USB supports plug-and-play printer identification 10/100 Ethernet connectivity

ELECTRICAL

Auto-switching AC power 90V~264V AC and 48 - 62 Hz

PHYSICAL CHARACTERISTICS	
Height	11.42" / 290 mm
Width	10.94" / 278 mm
Depth	19.09" / 485 mm
Weight (printer only)	46.3 lbs. / 21 kg

OPERATING CHARACTERISTICS

Environment	Operating Temperature: 50° F / 10° C to 95° F / 35° C
	Storage Temperature: -4° F / -20° C to 131° F / 55° C
	Operating Humidity: 20% to 80% inclusive, non-condensing
	Storage Humidity: 10% to 95% inclusive, non-condensing
	Shipping Temperature: -40° F / -40° C to 140° F / 60° C
	Shipping Humidity: 10% to 95% inclusive, non-condensing

NOTE: For optimum print quality and printer performance, use of Genuine Zebra supplies is recommended.

* Print speed does not include data transfer. Specifications provided are in an ambient room temperature with printer connected via USB connectivity, card

Specifications subject to change without notice.

www.abr.com

